

TUF-FEET BALL JOINT FEET

FEATURES

- Active ball suspension allows for optimal performance
- Rubber pad adds grip to prevent scale from sliding on or scraping the floor
- Includes 2 jam nuts
- UNF threading
- Top is slotted for applications with top access

PART #	MATERIAL	SIZE	THREAD	SHIP WT.
12100	Alloy Steel	2.4" D x 3.5" H	1/2" - 20 UNF	1.25 lbs
12101	Alloy Steel	3" D x 4.25" H	3/4" - 16 UNF	1.25 lbs
12102	Alloy Steel	3" D x 4.25" H	1" - 14 UNF	1.25 lbs
12103	Stainless Steel	2.4" D x 3.5" H	1/2" - 20 UNF	1.25 lbs
12104	Stainless Steel	3" D x 4.25" H	3/4" - 16 UNF	1.25 lbs
12105	Stainless Steel	3" D x 4.25" H	1" - 14 UNF	1.25 lbs

PARTS

PART #	ITEM	SIZE	SHIP WT.
12106	Replacement Rubber Pad	2.4" D x 0.5" H	1 lbs
12107	Replacement Rubber Pad	3.1" D x 0.75" H	1 lbs



DURA-FEET BALL JOINT FEET

FEATURES

- Active ball suspension allows for optimal performance
- Rubber pad adds grip to prevent scale from sliding on or scraping the floor
- Includes 2 jam nuts
- Top is slotted for applications with top access

PART #	MATERIAL	SIZE	THREAD	SHIP WT.
12114	Alloy Steel	3" D x 4" H	1/2" - 20 UNF	1.25 lbs
12115	Alloy Steel	3" D x 4" H	3/4" - 16 UNF	1.25 lbs
12116	Alloy Steel	3" D x 4.5" H	1" - 14 UNF	1.25 lbs
12117	Stainless Steel	3" D x 4" H	1/2" - 20 UNF	1.25 lbs
12118	Stainless Steel	3" D x 4" H	3/4" - 16 UNF	1.25 lbs
12119	Stainless Steel	3" D x 4.5" H	1" - 14 UNF	1.25 lbs



SUPRA-FEET BALL JOINT FEET

FEATURES

- Ball and socket allows for best accuracy from the load cell
- Rubber pad adds grip to prevent scale from sliding on or scraping the floor
- Includes 2 jam nuts
- Top is slotted for applications with top access

PART #	MATERIAL	SIZE	THREAD	SHIP WT.
12108	Alloy Steel	3" D x 3.75" H	1/2" - 20 UNF	1.25 lbs
12109	Alloy Steel	3" D x 4.5" H	3/4" - 16 UNF	1.25 lbs
12110	Alloy Steel	3" D x 4.5" H	1" - 14 UNF	1.25 lbs
12111	Stainless Steel	3" D x 3.75" H	1/2" - 20 UNF	1.25 lbs
12112	Stainless Steel	3" D x 4.5" H	3/4" - 16 UNF	1.25 lbs
12113	Stainless Steel	3" D x 4.5" H	1" - 14 UNF	1.25 lbs



RIGI-FEET RIGID FEET

FEATURES

- Rubber pad adds grip to prevent scale from sliding on or scraping the floor
- Includes 2 jam nuts
- UNF threading
- Top is slotted for applications with top access

PART #	MATERIAL	SIZE	THREAD	SHIP WT.
12120	Alloy Steel	3" D x 2.75" H	1/2" - 20 UNF	0.25 lbs
12121	Alloy Steel	3" D x 2.75" H	3/4" - 16 UNF	0.25 lbs
12122	Stainless Steel	3" D x 2.75" H	1/2" - 20 UNF	0.25 lbs



SQUAT-FEET LOW PROFILE RIGID FEET

FEATURES

- Small, low profile foot
- Bottom rubber pad adds grip to prevent scale from sliding on or scraping the floor
- Top is slotted for applications with top access

PART #	MATERIAL	SIZE	THREAD	SHIP WT.
12123	Alloy Steel	2" D x 2.5" H	1/2" - 20 UNF	0.75 lbs



AG-FEET LARGE FEET FOR AG APPLICATIONS

FEATURES

- Heavy duty large low profile feet with 1/2" anchor holes for ultimate security
- Used in agricultural applications
- Includes 2 jam nuts
- Top is slotted for applications with top access

PART #	MATERIAL	SIZE	THREAD	SHIP WT.
12124	Alloy Steel	5.85" D x 3" H	1/2" - 20 UNF	3.1 lbs



ANCHORING PLATE

FEATURES

- Foot retainers for anchoring your scale from moving
- Anchor plates to the ground with 1/2" bolts
- Place feet inside holes to prevent movement

PART #	COLOR	HOLE SIZE	SHIP WT.
12125	Black/Blue	2.57"	2 lbs
12126		3.15"	



BENCH-FEET ABS BENCH SCALE FEET

FEATURES

- ABS (Acrylonitrile Butadiene Styrene) bottom construction
- Alloy steel stem

PART #	MATERIAL	SIZE	THREAD	SHIP WT.
12127	Alloy Steel and ABS	2" D x 2" H	16 UNF	0.5 lbs



SS BENCH-FEET BENCH SCALE FEET

FEATURES

- All stainless steel construction
- For use with our washdown bench scales
- Bottom rubber pad adds grip to prevent scale from sliding on or scraping floor

PART #	MATERIAL	SIZE	THREAD	SHIP WT.
12128	Stainless Steel	2" D x 2" H	16 UNF	0.5 lbs



FOOD GRADE-FEET BENCH SCALE FEET

FEATURES

- All stainless steel construction
- For use with our washdown bench scales
- Bottom rubber adds grip to prevent scale from sliding on or scraping floor

PART #	MATERIAL	SIZE	THREAD	SHIP WT.
12129	Stainless Steel	2" D x 2" H	16 UNF	0.5 lbs

