

T900 INDICATOR

TUFNER

WEIGHING SYSTEMS



**T900A-MS LED
PAINTED MILD STEEL**



T900B-SS LCD



**T900B-SL LCD
NEMA 4X STAINLESS STEEL**



**T900A-SL LED
NEMA 4X WASHDOWN
STAINLESS STEEL**

FEATURES


- Indicator is constructed with a Painted Steel, Stainless Steel or IP67 NEMA 4X Washdown Stainless Steel enclosure
- 1" LED or LCD display with backlight
- Units: LED (lb, kg), LCD (lb, kg, oz, lb:oz, g)
- Color coded check weighing ● Over ● Accept ● Under LED lights
- Washdown version has an IP67 certification to withstand high pressure and high temperature water cleaning to 1450 psi and 176°F/80°C
- Gross/Tare/Pre-Set Tare/Zero & Multiple Hold functions
- Count weighing & Accumulation weighing
- Overload / Underload alarm
- Power saving mode
- Automatic date and time update
- Ability to modify gravity based on different geographical locations
- 100% manual zero range setting
- Automatic error warning alarm
- Splash proof keyboard and display
- NTEP approved for 5,000 divisions, displays up to 50,000 graduations
- 1" LED or LCD display with backlight
- Mounting bracket and Hardware (included)
- Operates on 110V AC adapter (included) Battery -100 hrs (optional)
- Multi-point calibration (up to 5 points)
- Full Duplex RS-232 Serial Port for printer/computer/scoreboards
- Drives up to 6 350Ω load cells
- 1 Year Warranty

OPTIONAL FEATURES

- LED or LCD display option
- Stainless steel or mild steel casing
- NEMA 4X Washdown casing
- Relay & Analog output
- 6V Rechargeable Battery
- Data Logging Software
- Wireless capability

ACCESSORIES

- Thermal Ticket Printer
- Label Printer
- Zebra Label Printer
- Remote Display
- Indicator Stand
- Stainless steel enclosure
- I/O Card to control external system



SPECIFICATIONS

Display:

LCD or LED; 1in. x 6 digit numeric

Units:

lb, kg (primary), oz, g (LCD only)

Accuracy Class:

5,000 e

Resolution:

120,000 dd industrial; 10,000 dd HB44

Excitation Voltage:

5V DC

Largest Output Current

120 mA

Excitation Circuit

5 VDC, 4-wire connections

Load Cell

6 load cells of 350 Ω maximum

Load Cell Excitation

5 ± 0.5VDC

Display Resolution

30,000; ADC: 2,000,000

Zero Stability Error

TKspn < ± 6 ppm/K

Sensitivity (Internal)

0.3 μV/d

Input Voltage

-30 to +30mV DC

Power

100~240VAC @ 50/60Hz

Power Consumption

5W @9VDC (Optional 12-24V Input)

Operating Temperature

14°F to 104°F ≤ 90%RH

Internal Resolution

24-bit A/D Sigma-Delta; 1,048,000 d

Display Increments

Selectable 1, 2, 5, 10, 20, 50

Conversion Rate

12 samples/second typical

Analog Signal Input Range

1mV/V to 3mV/V

Analog Signal Sensitivity

0.1 μV/graduation (min)

Measurement Rate

0 ~ 15mV

Auto Zero Tracking

0 - 5 dd increments

T900 INDICATOR



**T900P
BUILT-IN PRINTER**



**T900B-MS LCD
PAINTED CARBON STEEL**



**T900A-SS LED
STAINLESS STEEL**

PART#	DISPLAY	CASING	IP	POWER	CONNECTION	SHIP WT.
MILD STEEL						
T900A-MS-01	LED	Mild Steel	65	AC Adapter	Quick Disconnect	5 lbs
T900B-MS-01	LCD	Mild Steel	65	AC Adapter	Quick Disconnect	5 lbs
T900A-MS-02	LED	Mild Steel	65	AC Adapter & Battery	Quick Disconnect	5 lbs
T900B-MS-02	LCD	Mild Steel	65	AC Adapter & Battery	Quick Disconnect	5 lbs
STAINLESS STEEL						
T900A-SS-11	LED	Stainless Steel	65	AC Adapter	Quick Disconnect	5 lbs
T900B-SS-11	LCD	Stainless Steel	65	AC Adapter	Quick Disconnect	5 lbs
T900A-SS-12	LED	Stainless Steel	65	AC Adapter & Battery	Quick Disconnect	5 lbs
T900B-SS-12	LCD	Stainless Steel	65	AC Adapter & Battery	Quick Disconnect	5 lbs
WASHDOWN						
T900A-SL-13	LED	NEMA 4, Stainless Steel	66	Power Supply Only	Quick Disconnect	7 lbs
T900B-SL-13	LCD	NEMA 4, Stainless Steel	66	Power Supply Only	Quick Disconnect	7 lbs
T900A-SL-23	LED	NEMA 4, Stainless Steel	66	Power Supply & Battery	Hardwire	7 lbs
T900B-SL-23	LCD	NEMA 4, Stainless Steel	66	Power Supply & Battery	Hardwire	7 lbs
With Built-in Thermal Printer						
T900P-12	LED	Stainless Steel	65	AC Adapter & Battery	Quick Disconnect	8 lbs
With 4-20ma Relay Output						
T900A/O	LED	Mild Steel	65	AC Adapter	Quick Disconnect	5 lbs
With 0-5V Relay Output						
T900R/O	LED	Mild Steel	65	AC Adapter	Quick Disconnect	5 lbs

PARTS


PART#	ACCESSORY	SHIP WT.
12052	AC Adapter	1 lbs
12053	AC Adapter Water Sealed	1 lbs
12054	Battery	2 lbs
12055	PCB Board (LED)	1 lbs
12056	PCB Board (LCD)	1 lbs
12057	Faceplate (Overlay)	1 lbs
12058	Mounting Bracket	2 lbs
12059	Clear Plastic Indicator Face Cover	1 lbs



FACEPLATE (OVERLAY)



BATTERY



PCB BOARD



AC ADAPTER